



288W - 24V 3-Output Switching Power Supply OMS-EP288W-24V



Class 2
Made in Korea

Specifications

INPUT	VOLTAGE	AC90V - 277V
	AC CURRENT	3.2A
	FREQUENCY	50/60Hz
	INRUSH CURRENT	50A
	INPUT POWER	315W
	EFFICIENCY	≥92%
	POWER FACTOR	≥0.95
OUTPUT	VOLTAGE	24VDC
	RATED CURRENT	12A (4A per Output)
	LINE & LOAD REGULATION	+/-5%
	RIPPLE & NOISE(MAX)	350mVp-p
	SETUP, RISING TIME	1000ms @220Vac Full Load
	HOLD UP TIME	50ms @220Vac Full Load
PROTECTION	ENCLOSURE PROTECTION	IP68
	CLASS	Class 2
	SHORT CIRCUIT	Auto Restart
	OVER CURRENT	Auto Restart
	OVER TEMPERATURE	Latch mode
ISOLATION	WITH STAND VOLTAGE	I/P-O/P3.75kVac/10mA, I/P-Case 1.5kVac/10mA
	ISOLATION RESISTANCE	100MOhm Max/500Vdc
ENVIRONMENT	WORKING TEMP. & HUMIDITY	-4~122°F, 20~85%RH
	STORAGE TEMP. & HUMIDITY	-4~167°F, 5~95%RH
	DIMENSION (INCH)	10.2 x 2.7 x 1.8
	WEIGHT (LBS)	1.4
	CASE MATERIAL	Aluminum
	MOLDING MATERIAL	Silicon
	CERTIFICATE	UL879 - UL E528990
	QTY/CTN	10

