

Also known as LED Drivers, our SMPS units are top of the line. By utilizing switch mode, power efficiency is greatly increased over other brands.

- * Constant Voltage
- * Variable AC input 90-277 VAC
- * IP68 construction with waterproof enclosure
- * Suitable for Dry, Damp and Wet Location
- * Protection: Short Circuit / Over Temp. / Over Voltage
- * Metal Case except for FP60W
- * 100% full load burn-in test
- * 5 years warranty (3 years on FP series)
- * LLC current resonant technology with 92-96% efficiency, reduced size and increased reliability.
- * UL - E528990



FP60W12V / FP100W24V



60W / 12VDC, 100W / 24VDC
Class 2

FM60W12V



60W / 12VDC
Class 2

FM100W12V



100W / 12VDC
Class 1

FM150W12V



150W / 12VDC
Class 1

FM200W12V



200W / 12VDC
Class 1

FM300W12V



300W / 12VDC
Class 1

Part Number	Input Voltage	Output	Wattage	Class2	Size (inch)			Case	Enclosure	Warranty
					L	W	H			
FP-60W-12V	90-277VAC	12V / 5A	60W	✓	4.7	2.1	1.4	Plastic	IP62	3 years
FP-100W-24V	90-277VAC	24V / 4.15A	100W	✓	4.7	2.1	1.4	Plastic	IP62	3 years
FM-60W-12V	90-277VAC	12V / 5A	60W	✓	6.5	1.8	1.3	Aluminum	IP68	5 years
FM-100W-12V	90-277VAC	12V / 8.4A	100W	X	7.6	2.1	1.4	Aluminum	IP68	
FM-150W-12V	90-277VAC	12V / 12.5A	150W	X	8.8	2.1	1.4	Aluminum	IP68	
FM-200W-12V	90-277VAC	12V / 16.6A	200W	X	8.8	2.1	1.4	Aluminum	IP68	
FM-300W-12V	90-277VAC	12V / 25A	300W	X	9.6	2.6	1.7	Aluminum	IP68	